



# HAYDON®


Get Strut Done.

## C-440

### Electrical Beam Clamp

# Submittal Sheets

Catalog No.	Rod Size A	Set Screw B	C	D	Load Lbs.	Wt./100 Pcs.
C-440-1/4	1/4-20	5/16-18	1 3/8"	1 3/16"	150	24
C-440-5/16	5/16-18	3/8-16	1 3/8"	1 3/16"	150	24
C-440-3/8	3/8-16	1/2-13	1 7/8"	1 3/16"	350	65
C-440-1/2	1/2-13	1/2-13	2 3/8"	2 1/2"	1000	130



**MATERIAL:** Malleable Iron  
**FINISH:** Electro-Galvanized  
**APPLICATION:** Rod support for beams with a flange thickness of 1/2" max.  
**ORDERING:** Specify part # and rod size.

## Specifications

### GENERAL

H-STRUT General Fittings are designed to secure all H-STRUT 1 5/8" wide channels, or threaded rod, to beams or supports for the purpose of running piping, conduit or tubing. All H-STRUT fittings are manufactured from 1/4" thick carbon steel or cast malleable iron. Please contact the factory for any other clamps you may need.

### ORDERING

Please specify catalog number and finish.

### MATERIAL

H-STRUT fittings are manufactured from the following material:

- Hot Rolled Steel Sheet . . . . .ASTM A-1101 or Cold Rolled Steel Sheet . . . . .ASTM A-1008
- Stainless Steel-Type 304/316L. . . . .ASTM A-240
- Malleable Cast Iron

### FINISH

H-STRUT pipe clamps are available in the following finishes:

- Electro-Galvanized . . . . .ASTM B-633
- Hot Dipped Galvanized. . . . .ASTM A-123
- Zinc Trivalent Chromium. . . . .ASTM B-633-85
- Powder Coated Supr-Green. . . . .ASTM B-117
- PVC Coating - Available Upon Request

Project Information		
Project:		Notes:
Address:		
Contractor:		
Engineer:	Date:	
Approval		
<input type="checkbox"/> Approved	Signature:	Remarks:
<input type="checkbox"/> Approved as Noted		
<input type="checkbox"/> Not Approved		