


## 1000 Series

### End Cap

The 1000 Series End Cap is supplied on all Concrete Inserts longer than 12". End Caps may be ordered separately.



FINISH: Electro-Galvanized

Catalog No.	Use With H-STRUT	A	Wt./100 Pcs.
1000-EC-1	1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " 12-ga. Channel – H-132	1 $\frac{5}{8}$ "	7
1000-EC-2	1 $\frac{3}{4}$ " x 1 $\frac{5}{8}$ " 12-ga. Channel – H-142	1 $\frac{3}{8}$ "	6
1000-EC-3	1" x 1 $\frac{5}{8}$ " 12-ga. Channel – H-152	1"	4
1000-EC-5	1 $\frac{3}{16}$ " x 1 $\frac{5}{8}$ " 14-ga. Channel – H-164	1 $\frac{13}{16}$ "	4
1000-EC-6	2 $\frac{1}{16}$ " x 1 $\frac{5}{8}$ " 12-ga. Channel – H-122	2 $\frac{3}{8}$ "	16
1000-EC-7	3 $\frac{1}{4}$ " x 1 $\frac{5}{8}$ " 12 ga. Channel – H-112	3 $\frac{7}{32}$ "	19
1000-EC-8	1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " 14-ga. Channel – H-134	1 $\frac{5}{8}$ "	10

## SPECIFICATIONS

### GENERAL

H-STRUT Concrete Inserts are designed for the attachment or suspension of framing, piping or equipment to concrete structures where a continuous insert slot is required.

### LENGTH

H-STRUT Concrete Inserts are produced and stocked in 10 and 20 foot lengths. Other lengths are available upon request.

### ORDERING

Specify catalog number, length or size where required and finish when necessary.

### MATERIAL

H-STRUT Concrete Inserts and Accessories are produced from prime steel covering the following specifications:

- Hot Rolled Carbon Steel. . . . .ASTM A-1011-04-SS or Cold Rolled Carbon Steel . . . . .ASTM A-1008
- Stainless Steel - Type 304/316L. .ASTM A-240

### FINISH

H-STRUT Concrete Inserts and Accessories are stocked in the following finishes:

- Pre-Galvanized . . . . .ASTM A-653-G90
- Hot Dipped Galvanized. . . . .ASTM A-123
- Electro Galvanized . . . . .ASTM B-633

Project Information		
Project:		Notes:
Address:		
Contractor:		
Engineer:	Date:	
Approval		
<input type="checkbox"/> Approved	Signature:	Remarks:
<input type="checkbox"/> Approved as Noted		
<input type="checkbox"/> Not Approved		