


1001 Series

End Cap

The 1001 Series-Anchor End Cap is furnished on all Inserts up to 12" in length and provides nail lugs at each end of the Insert. End Caps may be ordered separately.

FINISH: Electro-Galvanized



Catalog No.	Use With H-STRUT	C	D	Wt./100 Pcs.
1001-EC-1	1 ⁵ / ₈ " x 1 ⁵ / ₈ " 12-ga. Channel – H-132	1.415	3 ¹ / ₈ "	22
1001-EC-2	1 ³ / ₄ " x 1 ⁵ / ₈ " 12-ga. Channel – H-142	1.165	2 ⁷ / ₈ "	20
1001-EC-3	1" x 1 ⁵ / ₈ " 12-ga. Channel – H-152	0.790	2 ¹ / ₂ "	18

SPECIFICATIONS

GENERAL

H-STRUT Concrete Inserts are designed for the attachment or suspension of framing, piping or equipment to concrete structures where a continuous insert slot is required.

LENGTH

H-STRUT Concrete Inserts are produced and stocked in 10 and 20 foot lengths. Other lengths are available upon request.

ORDERING

Specify catalog number, length or size where required and finish when necessary.

MATERIAL

H-STRUT Concrete Inserts and Accessories are produced from prime steel covering the following specifications:

- Hot Rolled Carbon Steel.ASTM A-1011-04-SS or Cold Rolled Carbon SteelASTM A-1008
- Stainless Steel - Type 304/316L. .ASTM A-240

FINISH

H-STRUT Concrete Inserts and Accessories are stocked in the following finishes:

- Pre-GalvanizedASTM A-653-G90
- Hot Dipped Galvanized.ASTM A-123
- Electro GalvanizedASTM B-633

Project Information			
Project:		Notes:	
Address:			
Contractor:			
Engineer:	Date:		
Approval			
<input type="checkbox"/> Approved	Signature:	Remarks:	
<input type="checkbox"/> Approved as Noted			
<input type="checkbox"/> Not Approved			