


## C-1104

### Universal Clamps



Nom. Size for E.M.T. Rigid Copper Clamps	O.D. Range Min./Max.	Wt./ 100 Pcs.	Std. Pkg.
3/8"	0.557 to 0.675	12	100
1/2"	0.706 to 0.840	13	100
3/4"	0.922 to 1.050	14	100
1"	1.163 to 1.315	18	100
1 1/4"	1.510 to 1.660	21	50
1 1/2"	1.740 to 1.900	23	50
2"	2.197 to 2.375	25	50

FINISH: Electro-Galvanized, other finishes available upon request.

ORDERING: Specify figure number and pipe size.

## SPECIFICATIONS

### GENERAL

H-STRUT Pipe Clamps are all manufactured to fit into the standard openings of 1 1/2" channel to support runs of piping where desired, to secure the pipe in place.

### MATERIAL

H-STRUT pipe clamps are manufactured from the following materials:

- Hot Rolled Steel Sheet . . . . .ASTM A-1011 or Cold Rolled Steel Sheet . . . . .ASTM A-1008
- Stainless Steel-Type 304/316 . . . . .ASTM A-240
- Aluminum Clamps 5052H32 . . . . .ASTM B-209

### FINISH

H-STRUT pipe clamps are available in the following finishes:

- Electro Galvanized . . . . .ASTM B-633
- Hot Dipped Galvanized. . . . .ASTM A-123
- Zinc Trivalent Chromium. . . . .ASTM B-633-85
- Powder Coated Supr-Green. . . . .ASTM B-117
- Copper Plated. . . . .ASTM B-734-84

### ORDERING

Please specify catalog number, size and finish.

Project Information			
<b>Project:</b>			<b>Notes:</b>
<b>Address:</b>			
<b>Contractor:</b>			
<b>Engineer:</b>	<b>Date:</b>		
Approval			
<input type="checkbox"/> <b>Approved</b> <input type="checkbox"/> <b>Approved as Noted</b> <input type="checkbox"/> <b>Not Approved</b>	<b>Signature:</b>		<b>Remarks:</b>