

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY	DTM White and Colors	Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.
----------	----------------------	--

Section I

Manufacturer's name	Emergency Telephone Number
US Specialty Coatings	404-408-0401
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information
1000 McFarland 400 Blvd	770-740-8549
Alpharetta, GA 30004	Date Prepared 07/13/2012
	Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

[illegible]

Section III—Physical/Chemical Characteristics

Boiling Point	180 +F	Specific Gravity (H ₂ O = 1)	1.39 Average
Vapor Density (AIR = 1)	Heavier than air	Evaporation Rate (Butyl Acetate = 1)	Slower than n-Butyl Acetate
Solubility in Water	100 %		
Appearance and Odor	White liquid and Mild odor		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) TCC/PM deg > F 200	Flammable Limits – not established	LEL	UEL
--	------------------------------------	-----	-----

Extinguishing Media	Dry Chemical
---------------------	--------------

Special Fire Fighting Procedures Keep Materials from heat, sparks, and open flames . USE WATER SPRAY TO COOL CONTAINERS EXPOSED TO HEAT OR FIRE TO PREVENT PRESSURE BUILD UP. SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED IF PRODUCT IS INVOLVED IN FIRE.

Unusual Fire and Explosion Hazards

Sensitivity to impact: PRODUCT WILL LEAK IF CONTAINER IS PUNCTURED.
(Reproduce locally) OSHA 174 Sept. 1985

Section V—Reactivity Data			
Stability	Unstable		Conditions to Avoid OPEN FLAMES, SPARKES AND ELECTRICAL ARCS
	Stable	X	
Incompatibility (Materials to Avoid) STRONG OXIDING AGENTS			
Hazardous Decomposition or Byproducts CARBON DIOXIDE AND CARBON MONOXIDE			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	
Section VI—Health Hazard Data			
Route(s) of Entry	Inhalation? respiratory tract irritant	Skin? prolonged contact may cause irritation	Ingestion? not likely with normal use
Health Hazards (Acute and Chronic)			
EYE CONTACT: PAINFUL WITH IRRITATION			
Carcinogenicity – INGREDIENTS ARE NOT LISTED AS CARCINOGEN	NTP? NA	IARC Monographs? NA	OSHA Regulated? NA
Signs and Symptoms of Exposure IRRITATION			
Medical Conditions Generally Aggravated by Exposure – NOT ESTABLISHED			
Emergency and First Aid Procedures			
Inhalation: Remove person to fresh air Skin Contact: Wash with soap and water			
Eye Contact: Flush eyes with water for at least 15 minutes, contact Physician			
Section VII—Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material Is Released or Spilled Remove all sources of ignition and ventilate vapors. Absorb with an inert material			
Waste Disposal Method Dispose in accordance with Federal, State, and Local Regulations			
Precautions to Be Taken in Handling and Storing Close containers after each us. Avoid damage to containers to prevent. spills.			
Keep material from heat, sparks and open flames. DO NOT STORE ABOVE 120 DEGREES F			
Other Precautions: DO NOT SMOKE WHILE USING THIS PRODUCT.			
Section VII—Control Measures			
Respiratory Protection Adequate ventilation is required. Use a respirator in confined areas, approved by U.S. Bureau of Mines.			
Ventilation	Local Exhaust	vapor concentration below T.V. and L.E.L.	Special
	Mechanical (General)		Other
Protective Gloves	Requires for prolonged contact		Eye Protection Use eye protection sufficient to prevent eye contact
Other Protective Clothing or Equipment NONE			
Work/Hygienic Practices			

DISCLAIMER

The information contained herein is based on data and information considered and believed to be accurate.