



Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

1 Identification

Product identifier

Trade name: Stobicoll® R 1136.99 Binder

Clear Black Urethane

Article number: 71136990

Relevant Color Codes: .99, .98, .97 - Indicates Differing Reactivity

Application of the substance / the mixture Binder

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Stockmeier Urethanes USA
20 Columbia Boulevard
Clarksburg, WV 26301-9606
USA
Telephone: (304) 624-7002
Fax: (304) 624-7020

Information department: Product Development Department

Emergency telephone number:

For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night.

Within USA and Canada: (800) 424-9300

Outside USA and Canada: +1 (703) 527-3887 (Collect Calls Not Accepted)

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Storage:

Store in a well-ventilated place. Keep container tightly closed. In closed containers, there may be a risk of pressure build up due to water contamination (Liberated CO2 Gas). Store locked up.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07



GHS08

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 1)

Signal word Danger

Hazard-determining components of labeling:

Extracts (petroleum), light paraffinic distillate solvent
4,4'-methylenediphenyl diisocyanate
methylenediphenyl diisocyanate (MDI) Mixed Isomers
Polymeric Diphenylmethane Diisocyanate

Hazard statements

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.
[In case of inadequate ventilation] wear respiratory protection.
Wear protective gloves.
Wear eye protection / face protection.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Rinse mouth.
IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed. In closed containers, there may be a risk of pressure build up due to water contamination (Liberated CO2 gas).
Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)

1	Health = 2
1	Fire = 1
2	Reactivity = 1

HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	1	Reactivity = 1

Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 2)

3 Composition/information on ingredients

Chemical characterization: Mixtures
Description: Aromatic Isocyanate Prepolymer

Dangerous components:

64742-05-8	Extracts (petroleum), light paraffinic distillate solvent	30 - 50%
101-68-8	4,4'-methylenediphenyl diisocyanate	10 - 20%
26447-40-5	methylenediphenyl diisocyanate (MDI) Mixed Isomers	1 - 5%
9016-87-9	Polymeric Diphenylmethane Diisocyanate	1 - 5%

Additional information:

CAS 101-68-8 is an MDI isomer that is a component of CAS 9016-87-9

CAS 101-68-8 is an MDI isomer that is a component of CAS 26447-40-5

4 First-aid measures

Description of first aid measures
General Information:

Symptoms of poisoning may even occur after several hours; therefore, medical observation is required for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of respiratory failure or breathing irregularities, commence resuscitation or administer oxygen.

In case of unconsciousness, place patient stably in side position for transportation.

After skin contact:

Instantly wash with water and soap and rinse thoroughly. Remove any contaminated clothing. If skin irritation persists, seek medical advice.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; immediately call for medical help.

Information for doctor:
Most important symptoms and effects, both acute and delayed

Diisocyanate vapors or mist at concentrations above the TLV or PEL can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the TLV or PEL with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the TLV or PEL may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g., fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

Acute Skin Contact: Causes irritation with symptoms of reddening, itching, and swelling. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

Chronic Skin Contact: Prolonged contact can cause reddening, swelling, rash, and, in some cases, skin sensitization. Animal tests and other research indicate that skin contact with diisocyanates can play a role in causing sensitization and respiratory reaction.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

Can be released in case of fire:

Nitrogen Oxides (NO_x)

Carbon Monoxide (CO)

Hydrogen Cyanide (HCN)

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 3)

Advice for firefighters

Protective equipment:

Wear breathing apparatus

Wear full protective suit with self-contained breathing apparatus

See section 8

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Down-wind personnel must be evacuated. Do not reseal moisture contaminated containers as a chemical reaction generating carbon dioxide gas may occur resulting in an increase of pressure which may rupture the container. Dense smoke is emitted when the product is burned without sufficient oxygen. When using water spray, boil-over may occur when product temperature reaches the boiling point of water and the reaction forming carbon dioxide will be accelerated. Diisocyanate vapors and other gases may be generated by thermal decomposition.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Clean-up should only be performed by trained personnel. Personnel dealing with major spills should wear appropriate protective equipment including, but not limited to, the following items: Gloves, goggles and respiratory protection equipment.

Environmental precautions: Do not allow product to reach sewage system or bodies of water.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Transfer to a waste container. Keep the material damp and exposed to the air in a secure area (CO₂-formation!) until completely solidified. The waste can then be disposed of on an approved landfill or a special refuse dump. Ensure adequate ventilation.

In the event of a large spill, treat spill area with decontamination solution. Preparation of decontamination solution: Prepare a mixture of 0.2 - 0.5% liquid detergent and 3 - 8% concentrated ammonium hydroxide in water (5 - 10% sodium carbonate may be substituted for the ammonium hydroxide).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Open and handle receptacle with care.

Keep containers tightly sealed.

Prevent formation of aerosols.

Exhaust ventilation required during spraying or when material is being used at temperatures above 100 degrees F.

Information about protection against explosions and fires:

Keep respiratory protective device available.

Pay attention to the general rules of internal fire prevention.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Recommended ideal storage temperature range: 59 - 77 degrees F. Product should not be stored below 40 degrees or above 110 degrees F.

Material can increase in viscosity if stored at lower temperatures for an extended period of time.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 4)

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

64742-05-8 Extracts (petroleum), light paraffinic distillate solvent	
TWA	Short-term value: 0.2 mg/m ³
101-68-8 4,4'-methylenediphenyl diisocyanate	
PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m ³ , 0.005 ppm
26447-40-5 methylenediphenyl diisocyanate (MDI) Mixed Isomers	
ACGIH TLV	Short-term value: 0.05 mg/m ³
NIOSH REL/CEILING	Short-term value: 0.2 mg/m ³
NIOSH REL/TWA	Short-term value: 0.05 mg/m ³
OSHA PEL	Short-term value: 0.2 mg/m ³

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Gases fumes and aerosols should not be inhaled.

Breathing equipment:

Airborne MDI concentrations greater than the ACGIH TLV-TWA (TLV) or OSHA PEL-C (PEL) can occur in inadequately ventilated environments when MDI is sprayed, aerosolized or heated. In such cases, respiratory protection must be worn. The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134). The type of respiratory protection available includes (1) an atmosphere-supplying respirator such as a self-contained breathing apparatus (SCBA) or a supplied air respirator (SAR) in the positive pressure or continuous flow mode, or (2) an air-purifying respirator (APR). If an APR is selected then (a) the cartridge must be equipped with an end-of-service life indicator (ESLI) certified by NIOSH, or (b) a change out schedule, based on the objective information or data that will ensure that the cartridges are changed out before the end of their service life, must be developed and implemented. The basis for the change out schedule must be described in the written respirator program. Further, if an APR is selected, the airborne diisocyanate concentration must be no greater than 10 times the TLV or PEL. The recommended APR cartridge is an organic vapor/particulate filter combination cartridge (OV/P100).

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The following glove types are recommended: neoprene, nitrile rubber, PVC or butyl rubber. Thin, disposable latex gloves should be avoided for repeated or long term handling of the material. Recommended thickness of the glove material: 5 - 6 mil
Selection of the glove material should be based on the consideration of penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 5)

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Liquid
Color:	Dark brown
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	>200 °C (>392 °F)
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not applicable.
Density at 20 °C (68 °F):	1.04 g/cm ³ (8.679 lbs/gal)
Relative density	Not determined.
Vapor density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Insoluble, Reacts
Partition coefficient (n-octanol/water):	
Not determined.	
Viscosity:	
Dynamic at 20 °C (68 °F):	850 mPas
Kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Solids content:	100.0 %
Other information	No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 6)

10 Stability and reactivity

Reactivity

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 F (177 C), may cause polymerization

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions

Exothermic reaction with amines and alcohols

Reacts with water to liberate CO₂ gas which may build pressure in closed containers

Conditions to avoid No further relevant information available.

Incompatible materials:

Exothermic reaction with amines and alcohols. Reacts with water forming heat, carbon dioxide and insoluble urea. The combined effect of carbon dioxide and heat can produce enough pressure to rupture a closed container.

Hazardous decomposition products:

By Fire and High Heat: Carbon Monoxide, Carbon Dioxide, Oxides of Nitrogen and traces of HCN.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

26447-40-5 methylenediphenyl diisocyanate (MDI) Mixed Isomers

Oral	LD50	> 5000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	> 5000 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4 h	2240 mg/l (rat)
------------	----------	-----------------

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

Possible carcinogen

Contains slight traces of ingredients that may cause cancer.

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

101-68-8	4,4'-methylenediphenyl diisocyanate	3
----------	-------------------------------------	---

9016-87-9	Polymeric Diphenylmethane Diisocyanate	3
-----------	--	---

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 7)

Additional ecological information:**General notes:**

Do not allow product to reach ground water, water course or sewage system.

This product is not miscible with water. Reacts with water at the interface producing CO₂ gas and forming a solid and insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (eg. detergents) or by water-soluble solvents. Previous experience demonstrates that polyurea is inert and non-degradable.

Water hazard class 2 (Self-assessment): hazardous for water

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Uncleaned packagings:**Recommendation:** Disposal must be made according to official regulations.**14 Transport information**

UN-Number	
DOT, ADR, ADN, IMDG, IATA	Void
UN proper shipping name	
DOT, ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA	
Class	Void
Packing group	
DOT, ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Danger code (Kemler):	-
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	Single containers less than 5,000 lbs are not regulated. Single containers with 5,000 lbs or more of 4,4'-methylenediphenyl diisocyanate are regulated as Class 9, NA 3082, PG III.
UN "Model Regulation":	Void

15 Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****Sara****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

64742-05-8 Extracts (petroleum), light paraffinic distillate solvent

101-68-8 4,4'-methylenediphenyl diisocyanate

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 8)

9016-87-9	Polymeric Diphenylmethane Diisocyanate
TSCA (Toxic Substances Control Act):	
64742-05-8	Extracts (petroleum), light paraffinic distillate solvent
101-68-8	4,4'-methylenediphenyl diisocyanate
26447-40-5	methylenediphenyl diisocyanate (MDI) Mixed Isomers
9016-87-9	Polymeric Diphenylmethane Diisocyanate

Proposition 65**Chemicals known to cause cancer:**

This material is formulated and specified using chemicals and raw materials not listed in the Safe Drinking Water and Toxic Enforcement Act of 1986, better known by its original name of California Proposition 65.

While this satisfies the directive, it must be understood that many of the chemicals and raw materials are industrial grade, and are subject to impurity and trace quantities of some of the restricted substances listed as prohibited by Prop 65. There is also the possibility that any component testing conducted by third parties could determine that some ingredients in certain combinations and concentrations appear to mimic chemicals on the Prop 65 list.

This product contains chemicals in trace quantities that are on the California Proposition 65 carcinogens list.

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Cancerogenity categories**EPA (Environmental Protection Agency)**

101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
9016-87-9	Polymeric Diphenylmethane Diisocyanate	CBD

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms**Signal word** Danger**Hazard-determining components of labeling:**

Extracts (petroleum), light paraffinic distillate solvent
4,4'-methylenediphenyl diisocyanate
methylenediphenyl diisocyanate (MDI) Mixed Isomers
Polymeric Diphenylmethane Diisocyanate

Hazard statements

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobicoll® R 1136.99 Binder

(Contd. of page 9)

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.
 [In case of inadequate ventilation] wear respiratory protection.
 Wear protective gloves.
 Wear eye protection / face protection.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Specific treatment (see on this label).
 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Wash contaminated clothing before reuse.
 IF exposed or concerned: Get medical advice/attention.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Rinse mouth.
 IF ON SKIN: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed. In closed containers, there may be a risk of pressure build up due to water contamination (Liberated CO₂ gas).
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Product Development Department

Contact: Product Development Department

Date of preparation / last revision 01/26/2017 / -

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Date of PDF Creation 01/26/2017

Reviewed on 01/26/2017

Trade name: Stobcoll® R 1136.99 Binder

(Contd. of page 10)

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

