

# **Submittal Sheets**


## 1000 Series

#### **End Cap**

The 1000 Series End Cap is supplied on all Concrete Inserts longer than 12". End Caps may be ordered separately.

FINISH: Electro-Galvanized

Catalog No.	Use With H-STRUT		Wt./100 Pcs.
1000-EC-1	1%" x 1%" 12-ga. Channel – H-132	15/8"	7
1000-EC-2	1¾" x 1½" 12-ga. Channel – H-142	13/8"	6
1000-EC-3	1" x 15/6" 12-ga. Channel – H-152	1"	4
1000-EC-5	<sup>13</sup> / <sub>16</sub> " x 1 <sup>5</sup> / <sub>8</sub> " 14-ga. Channel – H-164	<b>1</b> <sup>13</sup> / <sub>16</sub> "	4
1000-EC-6	2 <sup>7</sup> / <sub>16</sub> " x 1 <sup>5</sup> %" 12-ga. Channel – H-122	23/8"	16
1000-EC-7	3¼" x 15%" 12 ga. Channel – H-112	37/32"	19
1000-EC-8	15/8" x 15/8" 14-ga. Channel – H-134	15/8"	10



## **SPECIFICATIONS**

#### **GENERAL**

H-STRUT Concrete Inserts are designed for the attachment or suspension of framing, piping or equipment to concrete structures where a continuous insert slot is required.

#### **LENGTH**

H-STRUT Concrete Inserts are produced and stocked in 10 and 20 foot lengths. Other lengths are available upon request.

#### **ORDERING**

Specify catalog number, length or size where required and finish when necessary.

#### **MATERIAL**

H-STRUT Concrete Inserts and Accessories are produced from prime steel covering the following specifications:

☐ Hot Rolled Carbon Steel......ASTM A-1011-04-SS or Cold Rolled Carbon Steel.....ASTM A-1008
☐ Stainless Steel - Type 304/316..ASTM A-240

### FINISH

H-STRUT Concrete Inserts and Accessories are stocked in the following finishes:

Project Information					
Project:			Notes:		
Address:					
Contractor:					
Engineer:		Date:			
Approval Approval					
☐ Approved	Signature:		Remarks:		
☐ Approved as Noted					
☐ Not Approved					