


Submittal Sheets

A-323

"Z" Angle

| Catalog No. | A | Wt./100 Pcs. |
|----------------|---------------------------------|-----------------|
| A-323 | 1" | 50 |
| A-323-22 | 27/16" | 66 |
| A-323-42 | 13/8" | 53 |
| A-323-62 | ¹³ / ₁₆ " | 47 |



Specifications

GENERAL

H-STRUT General Fittings are designed to fit with all H-STRUT 1^5 /8" wide channels. All H-STRUT fittings are manufactured from 1/4" thick carbon steel, 1^5 /8" wide, all holes are 9/16" diameter, spaced 1^7 /8" on center and 1^3 /16" from the end.

MATERIAL

H-STRUT fittings are manufactured from the following material:

- ☐ Hot Rolled Steel Sheet ASTM A-1011 or Cold Rolled Steel Sheet ASTM A-1008
- ☐ Stainless Steel-Type 304/316L...ASTM A-240
- ☐ Aluminum Fitting......ASTM B-221

FINISHES

H-STRUT fittings are available in the following finishes: (See technical section for additional information)

- ☐ Electro Galvanized ASTM B-633
- ☐ Hot Dipped Galvanized. ASTM A-123
- ☐ Zinc Trivalent Chromium. ASTM B-633-85
- ☐ Powder Coated Supr-Green ASTM B-117
- □ PVC Coating Available Upon Request

ORDERING

Please specify catalog number and finish.

Fittings Notes

Holes are $\frac{9}{16}$ " diameter, spaced $1\frac{7}{8}$ " on center and $\frac{13}{16}$ " from end.

| Project Information | | | | | |
|---------------------|------------|-------|----------|--|--|
| Project: | | | Notes: | | |
| Address: | | | | | |
| Contractor: | | | | | |
| Engineer: | | Date: | | | |
| Approval Approval | | | | | |
| ☐ Approved | Signature: | | Remarks: | | |
| ☐ Approved as Noted | | | | | |
| ☐ Not Approved | | | | | |