
HAYDON
H-STRUT DIVISION

Submittal Sheets

B-630-FL

Double Column Post Base
Wt. 311#/C



Specifications

GENERAL

H-STRUT General Fittings are designed to fit with all H-STRUT 1⅝" wide channels. All H-STRUT fittings are manufactured from ¼" thick carbon steel, 1⅝" wide, all holes are 9/16" diameter, spaced 1⅞" on center and 13/16" from the end.

MATERIAL

H-STRUT fittings are manufactured from the following material:

- ❑ Hot Rolled Steel Sheet . . . . . .ASTM A-1011 or Cold Rolled Steel Sheet . . . . . .ASTM A-1008
- ❑ Stainless Steel-Type 304/316 . . .ASTM A-240
- ❑ Aluminum Fitting. . . . . .ASTM B-221

FINISHES

H-STRUT fittings are available in the following finishes: (See technical section for additional information)

- ❑ Electro Galvanized . . . . . .ASTM B-633
- ❑ Hot Dipped Galvanized. . . . . .ASTM A-123
- ❑ Zinc Trivalent Chromium. . . . . .ASTM B-633-85
- ❑ Powder Coated Supr-Green. . . .ASTM B-117
- ❑ PVC Coating - Available Upon Request

ORDERING

Please specify catalog number and finish.

Fittings Notes:

Holes are 9/16" diameter, spaced 1⅞" on center and 13/16" from end.

Project Information		
Project:		**Notes:**
Address:		
Contractor:		
Engineer:	**Date:**	

Approval		
❑ Approved	**Signature:**	**Remarks:**
❑ Approved as Noted		
❑ Not Approved		